

Pro Stock 4X4 Trucks

1. Maximum weight is 6,200 lbs. Add on weight is permissible. Hanging weight may not extend more than 195 inches from the center of the rear axle. Weights may not extend more than 60 inches from centerline of front axle. Two rollers must be attached to the most forward point of the bottom or side of weight box.
2. No cubic inch limit.
3. Any aluminum cylinder heads are permitted.
4. Aluminum blocks are permitted.
5. Single naturally aspirated carburetors only with no split or tunnel rams allowed.
6. Exhaust will exit thru hood or behind cab.
7. Sheet metal must conform to wheel base. Fiberglass body permitted. Must have a bed floor or tonneau cover and firewall.
8. Any make engine allowed with any make body.
9. Hitch height is 26" maximum. Must be rigid in all directions. No bolts in hitches. Must be forged pin. 3.75 x 3.5 opening. Secondary hitch is recommended but will be mandatory in 2022 pulling season. Any vehicle longer than 195 inches will have 25" hitch height for 2021 season. 27% hitch rule. Front point of hook to centerline of rear axle shall be no less than 27% of wheel base.
10. Rear of block must be 12" behind the center of front axle tube.
11. Drive train will consist of the following: Any front axle, any transfer case, any rear axle. No planetaries permitted.
12. OEM Frame rail only permitted.
13. Totally enclosed bell housing is required. Must meet SFI Spec 6.1 or better. All vehicles not inspected for highway use must have: manual transmission – Flywheel shield Automatic transmission – SFI Spec 29.1 flex plate. No cast iron permitted. A positive gear lockout, approved safety blanket over the torque converter area. A full-length blanket is required. Must meet SFI Spec 4.1. Drive shaft loops and U joint shields are required.
14. Maximum width of truck is 102"
15. No mud flaps or dirt deflectors.
16. Tires must be DOT approved. 35" x 12.50. No studded tires, chains, or any alterations. No bar tires and no dual tires.
17. Must have kill switch.
18. No fuel tanks or lines in cab.
19. All air or hydraulic suspension systems cannot have hydraulic; air or electrical lines attaches to these devices during competition.
20. Helmet, fire jacket and gloves are mandatory. No tennis shoes or open toes. Fire proof boots recommended.